

► Series AEB4H-IE

Progressing Cavity Pump in block design up to PN 25



► Pumped Liquid

Low to highly viscous liquids, pasty, neutral or aggressive, pure or abrasive, gaseous or tending to froth, also with fibrous and solids content

► Main Fields Of Application

Sewage and environmental engineering, chemical and petrochemical industries, food and beverages industry, paper and pulp industry, soap and fats industry, dye and paint industry, plastic and ceramics industry

► Performance Data

Capacity	Q	up to	200	l/min
Discharge Pressure	pd	up to	25	bar
Differential Pressure	pdiff	up to	24	bar
Viscosity	v	up to	270000	mm ² /s
Fluid temperature	t	up to	100	°C
No. Stages	-	up to	4	-

► Construction features

- Block design (Motor attached to pump via flange or lantern)
- Bulkhead mounting
- Pedestal mounting
- Dry installation
- Horizontal installation
- Directly coupled or belt gear or belt coupled driver
- Self-priming
- Reversible pumping

Document free of charge by phone +49 7732 86-382 fax +49 7732 86-99382

ALLWEILER AG
PO Box 1140
D-78315 Radolfzell Germany
Phone.: +49 (0)7732 86-0
Fax: +49 (0)7732 86-436
E-mail: service@allweiler.de
Internet: <http://www.allweiler.com>